



L642735830

LED GU10 MR16 50x54mm 100-250V
350Lm 5W 3000K 830 36° AC White Non-Dimmable

**Marine & Industry, Spot GU10 VR
100-250V Premium**



| General | | Energy | | |
|-----------------------------|--------------|-------------------------|----------------|----------------|
| Eprel registration no | 831580 | Volt | 100..250 V | |
| Socket | GU10 | Frequency | 50..60 Hz | |
| Bulb shape | MR16 | Watt | 5 W | |
| Width | 50.00 mm | Current type | AC | |
| Depth | 50.00 mm | Power factor | 0.5 | |
| Height | 54.00 mm | Energy efficiency class | G | |
| Finish | Clear | Energy consumption | 5 W | |
| Colour | Colourless | Lamp efficacy | 70.00 | |
| Colour housing | White | LED | | |
| Body material | Polycarbonat | Filament LED | No | |
| Lifespan | 15000 hours | LED type | SMD | |
| Switches | 50000 | Dimm type | Non-Dim | |
| Beam angle | 36 ° | Number of leds / sticks | 5 | |
| Dimmable | No | Colour consistency SDCM | SDCM5 | |
| Degree of protection | IP20 | Dim to warm | No | |
| Net weight | 0.032 kg | Adjustable beam angle | No | |
| Warranty | 3 years | Ordering details | | |
| Light | | L642735830 | Quantity pc(s) | EAN |
| Kelvin | 3000 K | Single package | 1 | 8718739056251 |
| Colour temp nr | 830 | Inner carton | 10 | 18718739056258 |
| Stable lumen | 450 lm | Outer carton | 100 | 28718739056255 |
| Lumen 90 cone | 350 lm | | | |
| Luminous intensity | 700 cd | | | |
| Color Rendering Index (CRI) | 82 | | | |

